

Double Electric Cargo Door

Model Number: USA-1000

Dual electric sliding cargo door, watertight to 22' head pressure.


*Custom sizes and pressures available upon request.


RATING: WT

CLEAR OPENING SIZE:

Tolerance ±1/8"

	Min	Max
"A"	78"	90"
"B"	78"	102"





POWER REQUIREMENTS:

 115VAC, 60Hz, 15 A (AVG: 920W)

WEIGHT:

Approx.: 4890 LB.

MINIMUM CLOSING TIME:

• TBD

FRAME FINISH OPTIONS:

- Bare Metal, Mill Finish
- Primer Paint
- Primer Base Coats
- Topcoat
- Powder Coat

OF DOG PINS:

• 12

DOOR MATERIAL:

- Mild Steel
- Aluminum

FRAME MATERIAL:

- Mild Steel (For Steel Door Only)
- Aluminum
 (For Aluminum Door Only)

GASKET:

Neoprene

ACTUATION:

Dual Electric

SAFETY FEATURES:

- Hazard Lights
- Hazard Buzzer

OPERATION:

- Manual (Hand Crank)
- Electrically Powered
- Locally Operated
- Bridge Controlled

CLASS OPTIONS:

(Vessel type and size rule set typically reviewed for Class)

- ABS
- DNV-GL
- IR

AVAILABLE DOCUMENTS:

- Wiring Diagrams
- Installation Manual















